Fall 2020 Qualifying Exam – Radiation Heat Transfer (Q1) – Closed Book

Assume black body radiation for all the three problems.

1. Find F_{12} for the arrangement shown below. The dimensions of the plates are provided in feet. Plates 3 and 4 are perpendicular to each other and share a common side.



2. Find the shape factor between the inside surfaces of the rectangular groove and the surroundings as shown below. Assume the depth of the groove perpendicular to the paper (or screen) is 3 m.



3. Find *F*₁₁ for the triangular groove of depth W (perpendicular to the paper (or screen)) shown below.





Fall 2020 Qualifying Exam – Conduction Heat Transfer (Q2) – Closed Book

A thin plate of width W (see figure) at room temperature is suddenly immersed in a hot fluid at time t = 0. Using the order of magnitude analysis (that was discussed in convection heat transfer in ME 540), derive the approximate expression for the time it takes for the heat to reach the center of the plate. Assume 1D heat conduction in the width direction and no internal heat generation in the plate.

Roughly draw the temperature profile in the plate, i.e., how does it vary in the plate between the two hot boundaries.



Energy Equation:

$$\frac{\partial}{\partial \mathbf{x}} \left(k \frac{\partial T}{\partial \mathbf{x}} \right) + \frac{\partial}{\partial y} \left(k \frac{\partial T}{\partial y} \right) + \frac{\partial}{\partial z} \left(k \frac{\partial T}{\partial z} \right) + \dot{q} = \rho \cdot c_p \frac{\partial T}{\partial t}$$

Fall 2020 Qualifying Exam – Thermodynamics (Q3) – Closed Book

In a cogeneration power plant, a heat engine is used to generate electricity and useful heat at the same time. A cogenerating solar power plant (as shown in figure below) operating with steam as the working fluid has a boiler output of 25 kg/s steam at 7 MPa, 500 °C. The condenser operates at 7.5 kPa and the process heat is extracted as 5 kg/s from the turbine at 500 kPa, state 6 and after use is returned as saturated liquid at 100 kPa, state 8. Assume all components are ideal and find the temperature after pump 1, the total turbine output and the total thermal process (between states 6 and 8) heat transfer.



Formula Sheet for Q3

- Volume flow rate Mass flow rate Flow work rate Flow direction
- $\dot{V} = \int \mathbf{V} \, dA = A \mathbf{V}$ (using average velocity) $\dot{m} = \int \rho \mathbf{V} \, dA = \rho A \mathbf{V} = A \mathbf{V} / v$ (using average values) $\dot{W}_{\text{flow}} = P \dot{V} = \dot{m} P v$ From higher P to lower P unless significant KE or PE exists

Instantaneous Process

Continuity equation	$\dot{m}_{\text{C.V.}} = \sum \dot{m}_i - \sum \dot{m}_e$
Energy equation	$\dot{E}_{C.V.} = \dot{Q}_{C.V.} - \dot{W}_{C.V.} + \sum \dot{m}_i h_{toti} - \sum \dot{m}_e h_{tote}$
Total enthalpy	$h_{\text{tot}} = h + \frac{1}{2} \mathbf{V}^2 + gZ = h_{\text{stagnation}} + gZ$

Steady State

No storage: $\dot{m}_{C.V.} = 0;$ $\dot{E}_{C.V.} = 0$

Continuity equation Energy equation Specific heat transfer Specific work energy equation

 $\sum \dot{m}_i = \sum \dot{m}_e$ (in = out) $\dot{Q}_{\mathrm{C.V.}} + \sum \dot{m}_i h_{\mathrm{tot}\,i} = \dot{W}_{\mathrm{C.V.}} + \sum \dot{m}_e h_{\mathrm{tot}\,e}$ (in = out) $q = \dot{Q}_{\rm CV} / \dot{m}$ (steady state only) $w = \dot{W}_{C.V.}/\dot{m}$ (steady state only) Steady-state, single-flow $q + h_{\text{tot }i} = w + h_{\text{tot }e}$ (in = out)

Steam Tables for Q3

TABLE A-5												
Saturated water-Pressure table												
		Spect	ric volume, n³/kg	Internal energy; KJ/kg				Enthalpy KJ/kg	;	Entropy; KJ/kg - K		
Press., P kPa	Sat. temp., 7 _{cat} °C	Sat. Ilquid, V _r	Sat. vapor, v _e	Sat. liquid, u _r	Evap., <i>u</i> a	Sat. vapor, u _g	Sat. Iiquid, <i>h_i</i>	Evap., n _e	Sat. vapor, n _g	Sat. Iiquid, s,	Evap., s _{ie}	Sat. vapor, s,
1.0	6.97	0.001000	129.19	29.302	2355.2	2384.5	29.303	2484.4	2513.7	0.1059	8.8690	8.9749
1.5	13.02	0.001001	87.964	54.686	2338.1	2392.8	54.688	2470.1	2524.7	0.1956	8.6314	8.8270
2.0	17.50	0.001001	66.990	73.431	2325.5	2398.9	73.433	2459.5	2532.9	0.2606	8.4621	8.7227
2.5	21.08	0.001002	54.242	88.422	2315.4	2403.8	88.424	2451.0	2539.4	0.3118	8.3302	8.6421
3.0	24.08	0.001002	45.654	100.98	2306.9	2407.9	100.98	2443.9	2544.8	0.3543	8.2222	8.5765
4.0	28.96	0.001004	34.791	121.39	2293.1	2414.5	121.39	2432.3	2553.7	0.4224	8.0510	8.4734
5.0	32.87	0.001005	28.185	137.75	2282.1	2419.8	137.75	2423.0	2560.7	0.4762	7.9176	8.2938
7.5	40.29	0.001008	19.233	168.74	2261.1	2429.8	168.75	2405.3	2574.0	0.5763	7.6738	8.2501
10	45.81	0.001010	14.670	191.79	2245.4	2437.2	191.81	2392.1	2583.9	0.6492	7.4996	8.1488
15	53.97	0.001014	10.020	225.93	2222.1	2448.0	225.94	2372.3	2598.3	0.7549	7.2522	8.0071
20	60.06	0.001017	7.6481	251.40	2204.6	2456.0	251.42	2357.5	2608.9	0.8320	7.0752	7.9073
25	64.96	0.001020	6.2034	271.93	2190.4	2462.4	271.96	2345.5	2617.5	0.8932	6.9370	7.8302
30	69.09	0.001022	5.2287	289.24	2178.5	2467.7	289.27	2335.3	2624.6	0.9441	6.8234	7.7675
40	75.86	0.001026	3.9933	317.58	2158.8	2476.3	317.62	2318.4	2636.1	1.0261	6.6430	7.6691
50	81.32	0.001030	3.2403	340.49	2142.7	2483.2	340.54	2304.7	2645.2	1.0912	6.5019	7.5931
75	91.76	0.001037	2.2172	384.36	2111.8	2496.1	384.44	2278.0	2662.4	1.2132	6.2426	7.4558
100	99.61	0.001043	1.6941	417.40	2088.2	2505.6	417.51	2257.5	2675.0	1.3028	6.0562	7.3589
101.325	99.97	0.001043	1.6734	418.95	2087.0	2506.0	419.06	2256.5	2675.6	1.3069	6.0476	7.3545
125	105.97	0.001048	1.3750	444.23	2068.8	2513.0	444.36	2240.6	2684.9	1.3741	5.9100	7.2841
150	111.35	0.001053	1.1594	466.97	2052.3	2519.2	467.13	2226.0	2693.1	1.4337	5.7894	7.2231
175	116.04	0.001057	1.0037	486.82	2037.7	2524.5	487.01	2213.1	2700.2	1.4850	5.6865	7.1716
200	120.21	0.001061	0.88578	504.50	2024.6	2529.1	504.71	2201.6	2706.3	1.5302	5.5968	7.1270
225	123.97	0.001064	0.79329	520.47	2012.7	2533.2	520.71	2191.0	2711.7	1.5706	5.5171	7.0877
250	127.41	0.001067	0.71873	535.08	2001.8	2536.8	535.35	2181.2	2716.5	1.6072	5.4453	7.0525
275	130.58	0.001070	0.65732	548.57	1991.6	2540.1	548.86	2172.0	2720.9	1.6408	5.3800	7.0207
300	133.52	0.001073	0.60582	561.11	1982.1	2543.2	561.43	2163.5	2724.9	1.6717	5.3200	6.9917
325	136.27	0.001076	0.56199	572.84	1973.1	2545.9	573.19	2155.4	2728.6	1.7005	5.2645	6.9650
350	138.86	0.001079	0.52422	583.89	1964.6	2548.5	584.26	2147.7	2732.0	1.7274	5.2128	6.9402
375	141.30	0.001081	0.49133	594.32	1956.6	2550.9	594.73	2140.4	2735.1	1.7526	5.1645	6.9171
400	143.61	0.001084	0.46242	604.22	1948.9	2553.1	604.66	2133.4	2738.1	1.7765	5.1191	6.8955
450	147.90	0.001088	0.41392	622.65	1934.5	2557.1	623.14	2120.3	2743.4	1.8205	5.0356	6.8561
500	151.83	0.001093	0.37483	639.54	1921.2	2560.7	640.09	2108.0	2748.1	1.8604	4.9603	6.8207
550	155.46	0.001097	0.34261	655.16	1908.8	2563.9	655.77	2096.6	2752.4	1.8970	4.8916	6.7886
600	158.83	0.001101	0.31560	669.72	1897.1	2566.8	670.38	2085.8	2756.2	1.9308	4.8285	6.7593
650	161.98	0.001104	0.29260	683.37	1886.1	2569.4	684.08	2075.5	2759.6	1.9623	4.7699	6.7322
700	164.95	0.001108	0.27278	696.23	1875.6	2571.8	697.00	2065.8	2762.8	1.9918	4.7153	6.7071
750	167.75	0.001111	0.25552	708.40	1865.6	2574.0	709.24	2056.4	2765.7	2.0195	4.6642	6.6837

TABLE A-6												
Superheated water												
T	V	и	h	s	V	u .	ħ	s	V	U.	h	5
°C	m-%g	k.J/kg	kJ/kg	kJ/kg ⋅ K	m-Ykg	k,J/kg	k.l/kg	kJ/kg · K	m-%g	k,l/kg	kJ/kg	k,Mg - K
	P - 0.01 MPa (45.81°C)*				P	a	P - 0.10 MPa (99.61°C)					
Sat.1	14.670	2437.2	2583.9	8.1488	3.2403	2483.2	2645.2	7.5931	1.6941	2505.6	2675.0	7.3589
100	17.196	2515.5	2687.5	8.4489	3.4187	2511.5	2682.4	7.6953	1.6959	2506.2	2675.8	7.3611
150	19.513	2587.9	2783.0	8.6893	3.8897	2585.7	2780.2	7.9413	1.9367	2582.9	2776.6	7.6148
200	21.826	2661.4	2879.6	8.9049	4.3562	2660.0	2877.8	8.1592	2.1724	2658.2	2875.5	7.8356
250	24.136	2736.1	2977.5	9.1015	4.8206	2735.1	2976.2	8.3568	2.4062	2733.9	2974.5	8.0346
300	26.446	2812.3	3076.7	9.2827	5.2841	2811.6	3075.8	8.5387	2.6389	2810.7	3074.5	8.2172
400	31.063	2969.3	3280.0	9.6094	6.2094	2968.9	3279.3	8.8659	3.1027	2968.3	3278.6	8.5452
500	35.680	3132.9	3489.7	9.8998	7.1338	3132.6	3489.3	9.1566	3.5655	3132.2	3488.7	8.8362
500	40.295	3303.3	3706.3	10.1631	8.05//	3303.1	3706.0	9.4201	4.02/9	3302.8	3705.6	9.0999
200	44.911	3400.0 3666 A	3929.9 4100.0	10.4000	0.9013	39800.0	3329.7 A100 A	9.0020	4.4900	3900.9 3665.0	3929.9	0.6299
ann	49.327	2855.0	4100.0	10.0312	10.8280	2856.8	4100.4	9.0003	5.4127	3856.7	4100.2	9.9962
1000	58 758	4055.3	4642.8	11 0429	11 7513	4055.2	46427	10.3000	5 8755	4055.0	4642.6	9 9800
1100	63.373	4260.0	4893.8	11.2326	12.6745	4259.9	4893.7	10.4897	6.3372	4259.8	4893.6	10.1698
1200	67.989	4470.9	5150.8	11.4132	13.5977	4470.8	5150.7	10.6704	6.7988	4470.7	5150.6	10.3504
1300	72.604	4687.4	5413.4	11.5857	14.5209	4687.3	5413.3	10.8429	7.2605	4687.2	5413.3	10.5229
	P - 0.20 MPa (120.21*C)				P	ω	P - 0.40 MPa (143.61°C)					
Sat.	0.88578	2529.1	2706.3	7.1270	0.60582	2543.2	2724.9	6.9917	0.46242	2553.1	2738.1	6.8955
150	0.95986	2577.1	2769.1	7.2810	0.63402	2571.0	2761.2	7.0792	0.47088	3 2564.4	2752.8	6.9306
200	1.08049	2654.6	2870.7	7.5081	0.71643	2651.0	2865.9	7.3132	0.53434	2647.2	2860.9	7.1723
250	1.19890	2731.4	2971.2	7.7100	0.79645	2728.9	2967.9	7.5180	0.59520	2726.4	2964.5	7.3804
300	1.31623	2808.8	3072.1	7.8941	0.87535	2807.0	3069.6	7.7037	0.65489	2805.1	3067.1	7.5677
400	1.54934	2967.2	3277.0	8.2236	1.03155	2966.0	3275.5	8.0347	0.77265	52964.9	3273.9	7.9003
500	1.78142	3131.4	3487.7	8.5153	1.18672	3130.6	3486.6	8.3271	0.88936	5 3129.8	3485.5	8.1933
600	2.01302	3302.2	3704.8	8.7793	1.34139	3301.6	3/04.0	8.5915	1.00558	\$ 3301.0	3/03.3	8.4580
700	2.244.34	3479.9	3328.8	9.0221	1.49580	34/9.5	3928.Z	8.8545	1.12152 1.92730	34/9.0	.3927.6	8.7012
000	2.47000	3004.7	4109.0	9.2479	1.00004	3004.3 29EC 0	4109.3	9.0000 0.979E	1.23730	3003.9 9966 7	4100.5	0.3274
1000	2 02755	A054.8	45397.7	9.4500	1 05824	4054.5	4642.0	0 4796	1 46850	10000.7	45350.5	0 2 2 0 5
1100	3 16848	4259.6	4893.3	9.8497	2 11226	4259.4	4893.1	9 6624	1 58414	4259.2	4892.9	9.5295
1200	3.39938	4470.5	5150.4	10.0304	2.26624	4470.3	5150.2	9.8431	1.69966	4470.2	5150.0	9,7102
1300	3.63026	4687.1	5413.1	10.2029	2.42019	4686.9	5413.0	10.0157	1.81516	4686.7	5412.8	9.8828
	P	0.50 MP	a (151.8	3°C)	P	Ω.	P - 0.80 MPa (170.41°C)					
Sat.	0.37483	2560.7	2748.1	6.8207	0.31560	2566.8	2756.2	6.7593	0.24035	2576.0	2768.3	6.6616
200	0.42503	2643.3	2855.8	7.0610	0.35212	2639.4	2850.6	6.9683	0.26088	2631.1	2839.8	6.8177
250	0.47443	2723.8	2961.0	7.2725	0.39390	2721.2	2957.6	7.1833	0.29321	2715.9	2950.4	7.0402
300	0.52261	2803.3	3064.6	7.4614	0.43442	2801.4	3062.0	7.3740	0.32416	2797.5	3056.9	7.2345
.350	0.57015	2883.0	3168.1	7.6346	0.47428	2881.6	3166.1	7.5481	0.35442	2878.6	3162.2	7.4107
400	0.61731	2963.7	3272.4	7.7956	0.51374	2962.5	3270.8	7.7097	0.38429	2960.2	3267.7	7.5735
500	0.71095	3129.0	3484.5	8.0893	0.59200	3128.2	3483.4	8.0041	0.44332	2 3126.6	3481.3	7.8692
600	0.80409	3300.4	3702.5	8.3544	0.66976	3299.8	3701.7	8.2695	0.50186	3298.7	3700.1	8.1354
700	0.89696	34/8.6	3927.0	8.5978	0./4725	34/8.1	3926.4	8.5132	0.56011	34/7.2	3925.3	8.3794
800	0.98966	3663.6	4158.4	8.8240	0.82457	3663.2	4157.9	8.7395	0.61820	3662.5	4157.0	8.6061
900	1.0822/	3855.4	43596.6	9.0062	0.90179	38555.1	4396.2	8.9518	0.5/619	4052.2	4395.5	0.0100
1100	1.1/480	4054.0	4641.4	9.2364	0.97893	4053.8	4641.1	9.1521	0.73411	4053.3	4640.5	9.0189
1200	1.20/20	4203.U	+dd2.6 51.40 P	0.6071	1 12200	0.0C3#	4002.4 51.40 C	0.5220	0.75157	A 038A	-4031.3 E140.3	0.3000
1300	1.30572	AERE E	5412.6	9 7797	1 21012	4686 A	5412 5	9,6955	0.90761	AGRE 1	5412.2	9 5695
0.450.002	1.4.96.14	THERE		a.e. 8.a.8	a	10000	10 T 2.2	and a second second	101010121023	THE PLACE	and the second	- 07

TABLE A-6

Superheated water (Continued) T 88 h φ. w 68 h M лr, h Ф. -92 °C m³/kg kJ/kg k.Mkg kJ/kg - K m3/kg k.Mez k.l/kg kJ/kg - K m³/kg kJ/kg kJ/kg kJ/kg - K P = 1.00 MPa (179.88°C) P = 1.20 MPa (187.96°C) P = 1.40 MPa (195.04°C) 2582.8 2777.1 6.5850 2788.9 6.4675 Sat. 0.19437 0.16326 2587.8 2783.8 6.5217 0.14078 2591.8 0.20602 2622.3 2828.3 6.6956 0.16934 2612.9 2816.1 6.5909 0.14303 2602.7 2803.0 6.4975 2000.23275 0.19241 2704.7 2935.6 6.8313 2927.9 6.7488 2502710.4 2943.1 6.9265 0.16356 2698.9 300 0.25799 2793.7 3051.6 7.1246 0.21386 2789.7 3046.3 7.0335 0.18233 2785.7 3040.9 6.9553 3158.2 7.3029 350 0.282502875.7 0.23455 2872.7 3154.2 7.2139 0.20029 2869.7 3150.1 7.1379 400 0.30661 2957.9 3264.5 7.4670 0.25482 2955.5 3261.3 7.3793 0.21782 2953.1 3258.1 7.3046 500 0.35411 3125.0 3479.1 7.7642 0.29464 3123.4 3477.0 7.6779 0.25216 3121.8 3474.8 7.6047 600 0.40111 3297.5 3698.6 8.0311 0.33395 3296.3 3697.0 7.9456 0.28597 3295.1 3695.5 7.8730 0.44783 3476.3 3924.1 8.2755 0.31951 700 0.37297 3475.3 3922.9 8.1904 3474.4 3921.7 8.1183 800 0.49438 3661.7 4156.1 8.5024 0.41184 3661.0 4155.2 8.4176 0.35288 3660.3 4154.3 8.3458 900 0.54083 3853.9 4394.8 8.7150 0.45059 3853.3 4394.0 8.6303 0.38614 3852.7 4393.3 8.5587 0.58721 4052.7 4640.0 8.9155 0.48928 4052.2 4639.4 8.8310 0.41933 1000 4051.7 4638.8 8.7595 1100 0.63354 4257.9 4891.4 9.1057 0.52792 4257.5 4891.0 9.0212 0.45247 4257.0 4890.5 8.9497 1200 0.67983 4469.0 5148.9 9.2866 0.56652 4468.7 5148.5 9.2022 0.48558 4468.3 5148.1 9.1308 1300 0.72610 4685.8 5411.9 9.4593 0.60509 4685.5 5411.6 9.3750 0.51866 4685.1 5411.3 9.3036 P - 2.00 MPa (212.38°C) P - 1.60 MPa (201.37°C) P - 1.80 MPa (207.11°C) 6.4200 0.12374 2594.8 2792.8 0.11037 2597.3 2795.9 6.3775 0.09959 2599.1 2798.3 6.3390 Sat. 6.5537 0.11678 2637.0 2847.2 6.4825 2628.5 2836.1 6.4160 225 0.13293 2645.1 2857.8 0.103816.6753 0.12502 6.6088 2500.14190 2692.9 2919.9 2686.7 2911.7 0.11150 2680.3 2903.3 6.5475 6.8864 0.14025 3029.9 6.8246 0.12551 2773.2 3024.2 6.7684 300 0.15866 2781.6 3035.4 2777.4 350 0.17459 2866.6 3146.0 7.0713 0.15460 2863.6 3141.9 7.0120 0.13860 2860.5 3137.7 6.9583 400 0.19007 2950.8 3254.9 7.2394 0.16849 2948.3 3251.6 7.1814 0.15122 2945.9 3248.4 7.1292 3472.6 7.5410 0.19551 3470.4 7.4845 3468.3 7.4337 500 0.22029 3120.1 3118.50.17568 3116.9 7.7543 600 0.24999 3293.9 3693.9 7.8101 0.22200 3292.7 3692.3 0.19962 3291.5 3690.7 7.7043 3919.4 8.0005 3918.2 7.9509 700 0.27941 3473.5 3920.5 8.0558 0.248223472.6 0.223263471.7 800 0.30865 3659.5 4153.4 8.2834 0.27426 3658.8 4152.4 8.2284 0.24674 3658.0 4151.5 8.1791 8.4965 900 0.33780 3852.1 4392.6 0.30020 3851.5 4391.9 8.4417 0.27012 3850.9 4391.1 8.3925 1000 0.36687 4051.2 4638.2 8.6974 0.32606 4050.7 4637.6 8.6427 0.29342 4050.2 4637.1 8.5936 11000.39589 4256.6 4890.0 8.8878 0.35188 4256.2 4889.6 8,8331 0.31667 4255.7 4889.1 8.7842 0.42488 4467.9 9.0689 0.37766 4467.6 5147.3 9.0143 0.33989 4467.2 5147.0 8.9654 12005147.7 0.45383 4684.8 5410.9 9.2418 4684.5 4684.2 1300 0.403415410.6 9.1872 0.36308 5410.3 9.1384 $P = 2.50 \text{ MPa} (223.95^{\circ}\text{C})$ P = 3.00 MPa (233.85°C) P = 3.50 MPa (242.56°C) 0.07995 2602.1 2801.9 6.2558 0.06667 2603.2 2803.2 6.1856 0.05706 2603.0 2802.7 6.1244 Sat. 225 0.08026 2604.8 2805.5 6.2629 250 0.08705 2663.3 2880.9 6.4107 0.07063 2644.7 2856.5 6.2893 0.05876 2624.0 2829.7 6.1764 300 0.09894 2762.2 3009.6 6.6459 0.08118 2750.8 2994.3 6.5412 0.06845 2738.8 2978.4 6.4484 0.09056 2844.4 6.7450 0.07680 2836.0 3104.9 6.6601 350 0.10979 2852.5 3127.0 6.8424 3116.1 400 0.12012 2939.8 3240.1 7.0170 0.09938 2933.6 3231.7 6.9235 0.08456 2927.2 3223.2 6.8428 450 0.13015 3026.2 3351.6 7.1768 0.10789 3021.2 3344.9 7.0856 0.09198 3016.1 3338.1 7.0074 500 0.13999 3112.8 3462.8 7.3254 0.11620 3108.6 3457.2 7.2359 0.09919 3104.5 3451.7 7.1593 600 0.15931 3288.5 3686.8 7.5979 0.13245 3285.5 3682.8 7.5103 0.11325 3282.5 3678.9 7.4357 3912.2 700 0.17835 3469.3 3915.2 7.8455 0.148413467.0 7.7590 0.12702 3464.7 3909.3 7.6855 800 0.19722 3656.2 4149.2 8.0744 0.16420 3654.3 4146.9 7.9885 0.14061 3652.5 4144.6 7.9156 0.17988 0.21597 3849.4 4389.3 8.2882 3847.9 4387.5 8.2028 900 0.15410 3846.4 4385.7 8.1304 1000 0.23466 4049.0 4635.6 8.4897 0.19549 4047.7 4634.2 8.4045 0.16751 4046.4 4632.7 8.3324 4253.6 1100 0.25330 4254.7 4887.9 8.6804 0.21105 4886.7 8.5955 0.18087 4252.5 4885.6 8.5236 0.27190 4466.3 5146.0 8.8618 0.22658 4465.3 5145.1 8.7771 0.19420 4464.4 5144.1 8.7053 1200 1300 0.29048 4683.4 5409.5 9.0349 0.24207 4682.6 5408.8 8.9502 0.20750 4681.8 5408.0 8.8786

TABLE	A-6											
Supert	heated wat	er (Conti	inued)									
T	v	u	h	s	v	u	h	s	v	u	h	s
°C	m ³ /kg	kJ/kg	k.l/kg	k.Mkg - K	m³/kg	k.l/kg	k.l/kg	k.Mkg - K	m ³ /kg	k.Mkg	kJ/kg	kJ/kg - K
	Р	PC)	Р	= 4.5 MP	a (257.44	10	P = 5.0 MPa (263.94°C)					
Sat.	0.04978	2601.7	2800.8	6.0696	0.04406	2599.7	2798.0	6.0198	0.03945	2597.0	2794.2	5.9737
275	0.05461	2668.9	2887.3	6.2312	0.04733	2651.4	2864.4	6.1429	0.04144	2632.3	2839.5	6.0571
300	0.05887	2726.2	2961.7	6.3639	0.05138	2713.0	2944.2	6.2854	0.04535	2699.0	2925.7	6.2111
350	0.06647	2827.4	3093.3	6.5843	0.05842	2818.6	3081.5	6.5153	0.05197	2809.5	3069.3	6.4516
400	0.07343	2920.8	3214.5	6.7714	0.06477	2914.2	3205.7	6.7071	0.05784	2907.5	3196.7	6.6483
450	0.08004	3011.0	3331.2	6.9386	0.07076	3005.8	3324.2	6.8770	0.06332	3000.6	3317.2	6.8210
500	0.08644	3100.3	3446.0	7.0922	0.07652	3096.0	3440.4	7.0323	0.06858	3091.8	3434.7	6.9781
600	0.09886	3279.4	3674.9	7.3706	0.08766	3276.4	3670.9	7.3127	0.07870	3273.3	3666.9	7.2605
700	0.11098	3462.4	3906.3	7.6214	0.09850	3460.0	3903.3	7.5647	0.08852	3457.7	3900.3	7.5136
800	0.12292	3650.6	4142.3	7.8523	0.10916	3648.8	4140.0	7.7962	0.09816	3646.9	4137.7	7.7458
900	0.13476	3844.8	4383.9	8.0675	0.11972	3843.3	4382.1	8.0118	0.10769	3841.8	4380.2	7.9619
1000	0.14653	4045.1	4631.2	8.2698	0.13020	4043.9	4629.8	8.2144	0.11715	4042.6	4628.3	8.1648
1100	0.15824	4251.4	4884.4	8.4612	0.14064	4250.4	4883.2	8.4060	0.12655	4249.3	4882.1	8.3566
1200	0.16992	4463.5	5143.2	8.6430	0.15103	4462.6	5142.2	8.5880	0.13592	4461.6	5141.3	8.5388
1300	0.18157	4680.9	5407.2	8.8164	0.16140	4680.1	5406.5	8.7616	0.14527	4679.3	5405.7	8.7124
	P - 6.0 MPa (275.59°C)					- 7.0 MP	a (285.83	-0	P - 8.0 MPa (295.01°C)			
Sat.	0.03245	2589.9	2784.6	5.8902	0.027378	2581.0	2772.6	5.8148	0.023525	2570.5	2758.7	5,7450
300	0.03619	2668.4	2885.6	6.0703	0.029492	2633.5	2839.9	5.9337	0.024279	2592.3	2786.5	5.7937
350	0.04225	2790.4	3043.9	6.3357	0.035262	2770.1	3016.9	6.2305	0.029975	2748.3	2988.1	6.1321
400	0.04742	2893.7	3178.3	6.5432	0.039958	2879.5	3159.2	6.4502	0.034344	2864.6	3139.4	6.3658
450	0.05217	2989.9	3302.9	6.7219	0.044187	2979.0	3288.3	6.6353	0.038194	2967.8	3273.3	6.5579
500	0.05667	3083.1	3423.1	6.8826	0.048157	3074.3	3411.4	6.8000	0.041767	3065.4	3399.5	6.7266
550	0.06102	3175.2	3541.3	7.0308	0.051966	3167.9	3531.6	6.9507	0.045172	3160.5	3521.8	6.8800
600	0.06527	3267.2	3658.8	7.1693	0.055665	3261.0	3650.6	7.0910	0.048463	3254.7	3642.4	7.0221
700	0.07355	3453.0	3894.3	7.4247	0.062850	3448.3	3888.3	7.3487	0.054829	3443.6	3882.2	7.2822
800	0.08165	3643.2	4133.1	7.6582	0.069856	3639.5	4128.5	7.5836	0.061011	3635.7	4123.8	7.5185
900	0.08964	3838.8	4376.6	7.8751	0.076750	3835.7	4373.0	7.8014	0.067082	3832.7	4369.3	7.7372
1000	0.09756	4040.1	4625.4	8.0786	0.083571	4037.5	4622.5	8.0055	0.073079	4035.0	4619.6	7.9419
1100	0.10543	4247.1	4879.7	8.2709	0.090341	4245.0	4877.4	8.1982	0.079025	4242.8	4875.0	8.1350
1200	0.11326	4459.8	5139.4	8.4534	0.097075	4457.9	5137.4	8.3810	0.084934	4456.1	5135.5	8.3181
1300	0.12107	4677.7	5404.1	8.6273	0.103781	4676.1	5402.6	8.5551	0.090817	4674.5	5401.0	8.4925

Fall 2020 Qualifying Exam – Convection Heat Transfer (Q4) – Closed Book

Assume hypothetically that the velocity profile u(y) in the boundary layer for the flow of air over a flat plate (with a free stream velocity (U) of 1 m/s) at a distance of 1 m from the leading edge of the plate is given by:

$$u(y) = 67y - 68600y^3$$
 in m/s

Using Reynolds-Colburn analogy,

$$\frac{h_x}{\rho c_p U} P r^{2/3} = \frac{\tau_w}{4\rho U^2}$$

find (1) the wall shear stress τ_w , (2) the local heat transfer coefficient h_x , and (3) the local Nusselt number at this location.

Use the following properties for air.

P=1.1777 kg/m³; μ = 0.2 x 10⁻⁴ Pa·s; c_p = 1009 J/kg·K; *k*= 0.029 W/m·K; *Pr* = 0.7

$$\tau_w = \mu \left[\frac{du}{dy} \right]_{y=0}$$

$$Nu_x = \frac{h_x \cdot x}{k}$$

$$Pr = \frac{\mu \cdot c_p}{k}$$